

DIGIMATIC SAND EQUIVALENT SHAKER

Standard: EN 933-8, ASTM D2419, AASHTO T176, NF XP18-598, UNE 83131, UNI 8520-15, CNR N.27

Assessment of Fine

The digimatic sand equivalent shaker features consist of digimatic timer (can be set at required time) to increase accuracy and ease of operation compared to a spring-type timer. The unit provides adjustable oscillation speed to confirm with both ASTM & EN test procedure,also eliminating variations from on operator to the next. The unit provides a consistent and repeatable oscillation, eliminating variations from one operator to the next.

Technical Specifications :

Model Number	NL 1001 X / 004
Speed Of Strokes	175 - 180 strokes / min
Dimension	770 (L) x 350 (W) x 435 (H) mm
Packing Dimension	830 (L) x 490 (W) x 480 (H) mm
Approx. Weight	44 kg
Packing Weight	55 kg
Power	220 VAC, 50 / 60 Hz, 0.8 A, 1 ph,128 W

Optional Accessories :

Model Number	Parts Description
NL 1000 X / 002	Sand Equivalent Apparatus



Timer



Single Cylinder



NL 1000 X / 002

41 Killarney Avenue, Killarney Gardens, Cape Town, 7441

021 839 5163

sales@capelab.co.za
info@capelab.co.za